

# Acrylic sealants

## SIL-AKR..



### Description

An acrylic-based sealing product for round ventilation ducts. The product contains no harmful solvents or odours. Once installed, the duct seal provides flexible joints, which can be coated with paint, ensuring excellent adhesion to galvanized steel sheets, coated steel sheets or stainless steel sheets. Once the duct seal compound has cured, it resists varying weather conditions. The product is intended for indoor and outdoor use. When fully cured, the duct seal compound is waterproof.


#### Product code example

Product code: **SIL-AKR-5K**


type \_\_\_\_\_

### Dimensions

Volume: 5 l and 20 l



Volume: 310 ml



Volume	ØD (mm)	H (mm)
310 ml	50	340
5L	200	320
20L	320	320

### Technical specifications

Product code	Volume	Material	Density	Method of application	Thermal resistance	Colour	Intended use
SIL-AKR-5K	5 l	acrylic compound	1.05 kg/l	brush	-40°C to +80°C (100°C)	silver grey	sealing of round ducts and fittings
SIL-AKR-20L	20 l	acrylic compound	1.5 kg/l	PIS-POMP	-40°C to +70°C	grey	sealing of round and square ducts and fittings
SIL-AKR-310	310 ml	acryl	1.5 kg/l	PIS-REC	-40°C to +80°C	grey	sealing of round and square ducts and fittings